

B180-06D3



- ↳ Compact 1-pair surge protection unit
- ↳ 6 V
- ↳ Removable protection circuit
- ↳ Wall mounting and screw connection
- ↳ UL497 A&B



	<p><b>Electrical Characteristics</b></p> <table border="1"> <tr> <td>Network</td> <td></td> <td>RS422, RS485</td> </tr> <tr> <td>Nominal line voltage</td> <td>Un</td> <td>6 V</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>Uc</td> <td>8 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>&gt; 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>&lt; 1 dB</td> </tr> <tr> <td>Max. discharge current max. withstand @ 8/20 μs by pole</td> <td>I<sub>max</sub></td> <td>20 kA</td> </tr> <tr> <td>Protection mode(s)</td> <td></td> <td>Common/Differential mode</td> </tr> <tr> <td>Protection levelFollowing the test category C3 (IEC61643-21) - Line/Line</td> <td>Up</td> <td>20 V</td> </tr> <tr> <td>Protection levelFollowing the test category C3 (IEC61643-21) - Line/PE</td> <td>Up</td> <td>20 V</td> </tr> <tr> <td>Line resistance</td> <td></td> <td>&lt; 4.7 Ohm</td> </tr> </table>	Network		RS422, RS485	Nominal line voltage	Un	6 V	Max. DC operating voltage	Uc	8 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	20 kA	Protection mode(s)		Common/Differential mode	Protection levelFollowing the test category C3 (IEC61643-21) - Line/Line	Up	20 V	Protection levelFollowing the test category C3 (IEC61643-21) - Line/PE	Up	20 V	Line resistance		< 4.7 Ohm			
Network		RS422, RS485																																
Nominal line voltage	Un	6 V																																
Max. DC operating voltage	Uc	8 Vdc																																
Max. frequency	f max.	> 3 MHz																																
Insertion loss		< 1 dB																																
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	20 kA																																
Protection mode(s)		Common/Differential mode																																
Protection levelFollowing the test category C3 (IEC61643-21) - Line/Line	Up	20 V																																
Protection levelFollowing the test category C3 (IEC61643-21) - Line/PE	Up	20 V																																
Line resistance		< 4.7 Ohm																																
<p>G: 3-electrode gas tube R: Resistor D3: 3-pole clamping diode</p>	<p><b>Mechanical Characteristics</b></p> <table border="1"> <tr> <td>Technology</td> <td></td> <td>GDT+Clamping diode</td> </tr> <tr> <td>SPD configuration</td> <td></td> <td>1 pair</td> </tr> <tr> <td>Connection to Network</td> <td></td> <td>By screw terminal: cross section 0.4-1.5mm<sup>2</sup></td> </tr> <tr> <td>Format</td> <td></td> <td>Wall mounting box</td> </tr> <tr> <td>Mounting</td> <td></td> <td>Wall mounting by screws (not supplied)</td> </tr> <tr> <td>Housing material</td> <td></td> <td>Thermoplastic UL94 V-0</td> </tr> <tr> <td>Operating temperature</td> <td>Tu</td> <td>-40/+85°C</td> </tr> <tr> <td>Protection rating</td> <td></td> <td>IP20</td> </tr> <tr> <td>Failsafe mode</td> <td></td> <td>Short-circuit - transmission cut-off - fault mode 2</td> </tr> <tr> <td>Spare module(s)</td> <td></td> <td>S180-06D3</td> </tr> <tr> <td>Dimensions</td> <td></td> <td>See diagram</td> </tr> </table>	Technology		GDT+Clamping diode	SPD configuration		1 pair	Connection to Network		By screw terminal: cross section 0.4-1.5mm <sup>2</sup>	Format		Wall mounting box	Mounting		Wall mounting by screws (not supplied)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Short-circuit - transmission cut-off - fault mode 2	Spare module(s)		S180-06D3	Dimensions		See diagram
Technology		GDT+Clamping diode																																
SPD configuration		1 pair																																
Connection to Network		By screw terminal: cross section 0.4-1.5mm <sup>2</sup>																																
Format		Wall mounting box																																
Mounting		Wall mounting by screws (not supplied)																																
Housing material		Thermoplastic UL94 V-0																																
Operating temperature	Tu	-40/+85°C																																
Protection rating		IP20																																
Failsafe mode		Short-circuit - transmission cut-off - fault mode 2																																
Spare module(s)		S180-06D3																																
Dimensions		See diagram																																
<p><b>Standards</b></p> <table border="1"> <tr> <td>Standards compliance</td> <td></td> <td>IEC 61643-21 / EN 61643-21 / UL497A</td> </tr> <tr> <td>Certification</td> <td></td> <td>UL listed</td> </tr> </table>		Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A	Certification		UL listed																											
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497A																																
Certification		UL listed																																
<p><b>Part number</b></p> <table border="1"> <tr> <td>Part number</td> <td></td> <td>510102</td> </tr> </table>		Part number		510102																														
Part number		510102																																