

CXP09-NW/MF/DCB



- ↳ Coaxial surge protector low frequency
- ↳ I<sub>max</sub> : 20 kA
- ↳ Up to 1 GHz
- ↳ Connector N



Electrical Characteristics		
Network		Coaxial 125-1000 MHz
Nominal line voltage	Un	< 50 V
Max. DC operating voltage	Uc	< 60 Vdc
Max. frequency	f max.	125-1000 MHz
Insertion loss		< 1 dB
Return loss		> 20 dB
Impedance		50 ohms
VSWR		<1.2:1
Max. load current	IL	0.5 A
Max. discharge current max. withstand @ 8/20 μs by pole	I <sub>max</sub>	20 kA
Protection mode(s)		Common mode/Differential mode
Protection level @ In (8/20μs)	Up	< 600 V
Impulse current <sup>2</sup> x 10/350μs Test - D1 Category	I <sub>imp</sub>	2.5 kA
Nominal discharge current <sup>2</sup> Category	I <sub>n</sub>	5 kA
Max Power		25 W
Insulation resistance	IR	≥10 GOhms
Mechanical Characteristics		
Technology		GDT+Filter
DC Block		Yes
Connection to Network		Connector N Male/Female
Format		Metallic box
Mounting		On plate
Housing material		Brass
Operating temperature	Tu	-40/+85°C
Protection rating		IP55
Outdoor application		No
Failsafe mode		Short-circuit
Disconnection indicator		Transmission interrupt
Dimensions		See diagram
Standards		
Standards compliance		IEC 61643-21 / EN 61643-21 / UL497C / UL497E
Part number		
6316531		