



DS252VG-400



- Type 1+2+3 unipolar surge protector
- 25 kA on 10/350µs impulse
- Low voltage Up
- Internal disconnection, status indicator and remote signaling
- Optimized to TOV
- IEC 61643-11 and UL1449 ed.5 compliance



	Electrical Characteristics																																																																						
 <p>V: High-energy varistor GSG: Specific gas tube Ft: Thermal fuse C: Remote signaling contact t*: Thermal disconnection system MI: Disconnection indicator</p>	<table border="1"> <tr><td>SPD type</td><td></td><td>1+2+3</td></tr> <tr><td>Network</td><td></td><td>230 V single-phase</td></tr> <tr><td>AC system</td><td></td><td>IT</td></tr> <tr><td>Nominal line voltage</td><td>Un</td><td>230/400 Vac</td></tr> <tr><td>Max. AC operating voltage</td><td>Uc</td><td>440 Vac</td></tr> <tr><td>Max. load current if series connection</td><td>IL</td><td>100 A</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection</td><td>UT</td><td>580 Vac withstand</td></tr> <tr><td>Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection</td><td>UT</td><td>770 Vac withstand</td></tr> <tr><td>Residual Current Leakage current to Ground</td><td>Ipe</td><td>None</td></tr> <tr><td>Follow current</td><td>If</td><td>None</td></tr> <tr><td>Nominal discharge current 15 x 8/20 µs impulses</td><td>In</td><td>30 kA</td></tr> <tr><td>Max. discharge current max. withstand @ 8/20 µs by pole</td><td>I_{max}</td><td>70 kA</td></tr> <tr><td>Impulse current by pole max. withstand 10/350µs by pole</td><td>I_{imp}</td><td>25 kA</td></tr> <tr><td>Total lightning current max. total withstand @ 10/350µs</td><td>I_{total}</td><td>50 kA</td></tr> <tr><td>Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs</td><td>Uoc</td><td>20 kV</td></tr> <tr><td>Withstand on overvoltages IEEE C62.41.1</td><td></td><td>20 kV</td></tr> <tr><td>Specific energy by pole max. withstand 10/350 µs</td><td>W/R</td><td>156 kJ/ohm</td></tr> <tr><td>Connection mode(s)</td><td></td><td>L/PE and N/PE</td></tr> <tr><td>Protection mode(s)</td><td></td><td>Common mode/Differential mode</td></tr> <tr><td>Residual voltage @ In (8/20 µs)</td><td>Up-in</td><td>1.1 kV</td></tr> <tr><td>Protection level N/PE @ In (8/20µs)</td><td>Up N/PE</td><td>1.5 kV</td></tr> <tr><td>Protection level L/PE @ In (8/20µs)</td><td>Up L/PE</td><td>1.5 kV</td></tr> <tr><td>Admissible short-circuit current</td><td>I_{sc}</td><td>50 000 A</td></tr> </table>		SPD type		1+2+3	Network		230 V single-phase	AC system		IT	Nominal line voltage	Un	230/400 Vac	Max. AC operating voltage	Uc	440 Vac	Max. load current if series connection	IL	100 A	Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	580 Vac withstand	Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	770 Vac withstand	Residual Current Leakage current to Ground	Ipe	None	Follow current	If	None	Nominal discharge current 15 x 8/20 µs impulses	In	30 kA	Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	70 kA	Impulse current by pole max. withstand 10/350µs by pole	I _{imp}	25 kA	Total lightning current max. total withstand @ 10/350µs	I _{total}	50 kA	Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	20 kV	Withstand on overvoltages IEEE C62.41.1		20 kV	Specific energy by pole max. withstand 10/350 µs	W/R	156 kJ/ohm	Connection mode(s)		L/PE and N/PE	Protection mode(s)		Common mode/Differential mode	Residual voltage @ In (8/20 µs)	Up-in	1.1 kV	Protection level N/PE @ In (8/20µs)	Up N/PE	1.5 kV	Protection level L/PE @ In (8/20µs)	Up L/PE	1.5 kV	Admissible short-circuit current	I _{sc}	50 000 A
SPD type		1+2+3																																																																					
Network		230 V single-phase																																																																					
AC system		IT																																																																					
Nominal line voltage	Un	230/400 Vac																																																																					
Max. AC operating voltage	Uc	440 Vac																																																																					
Max. load current if series connection	IL	100 A																																																																					
Temporary Over Voltage (TOV) Characteristics - 5 sec. Without disconnection	UT	580 Vac withstand																																																																					
Temporary Over Voltage (TOV) Characteristics - 120 mn Without disconnection or with safety disconnection	UT	770 Vac withstand																																																																					
Residual Current Leakage current to Ground	Ipe	None																																																																					
Follow current	If	None																																																																					
Nominal discharge current 15 x 8/20 µs impulses	In	30 kA																																																																					
Max. discharge current max. withstand @ 8/20 µs by pole	I _{max}	70 kA																																																																					
Impulse current by pole max. withstand 10/350µs by pole	I _{imp}	25 kA																																																																					
Total lightning current max. total withstand @ 10/350µs	I _{total}	50 kA																																																																					
Withstand on Combination waveform IEC 61643-11 Class III test: 1.2/50µs - 8/20µs	Uoc	20 kV																																																																					
Withstand on overvoltages IEEE C62.41.1		20 kV																																																																					
Specific energy by pole max. withstand 10/350 µs	W/R	156 kJ/ohm																																																																					
Connection mode(s)		L/PE and N/PE																																																																					
Protection mode(s)		Common mode/Differential mode																																																																					
Residual voltage @ In (8/20 µs)	Up-in	1.1 kV																																																																					
Protection level N/PE @ In (8/20µs)	Up N/PE	1.5 kV																																																																					
Protection level L/PE @ In (8/20µs)	Up L/PE	1.5 kV																																																																					
Admissible short-circuit current	I _{sc}	50 000 A																																																																					
Mechanical Characteristics																																																																							
<table border="1"> <tr><td>Technology</td><td></td><td>VG Technology (MOV+GSG)</td></tr> <tr><td>SPD configuration</td><td></td><td>Single phase</td></tr> <tr><td>Connection to Network</td><td></td><td>By screw terminals: 6-35mm² / by bus</td></tr> <tr><td>Format</td><td></td><td>1-pole modular box assembled</td></tr> <tr><td>Mounting</td><td></td><td>Symmetrical rail 35 mm (EN 60715)</td></tr> <tr><td>Housing material</td><td></td><td>Thermoplastic UL94 V-0</td></tr> <tr><td>Operating temperature</td><td>Tu</td><td>-40/+85°C</td></tr> <tr><td>Protection rating</td><td></td><td>IP20</td></tr> <tr><td>Failsafe mode</td><td></td><td>Disconnection from AC network</td></tr> <tr><td>Disconnection indicator</td><td></td><td>1 mechanical indicator by pole</td></tr> <tr><td>Remote signaling of disconnection</td><td></td><td>Output on changeover contact</td></tr> <tr><td>Dimensions</td><td></td><td>See diagram</td></tr> </table>			Technology		VG Technology (MOV+GSG)	SPD configuration		Single phase	Connection to Network		By screw terminals: 6-35mm ² / by bus	Format		1-pole modular box assembled	Mounting		Symmetrical rail 35 mm (EN 60715)	Housing material		Thermoplastic UL94 V-0	Operating temperature	Tu	-40/+85°C	Protection rating		IP20	Failsafe mode		Disconnection from AC network	Disconnection indicator		1 mechanical indicator by pole	Remote signaling of disconnection		Output on changeover contact	Dimensions		See diagram																																	
Technology		VG Technology (MOV+GSG)																																																																					
SPD configuration		Single phase																																																																					
Connection to Network		By screw terminals: 6-35mm ² / by bus																																																																					
Format		1-pole modular box assembled																																																																					
Mounting		Symmetrical rail 35 mm (EN 60715)																																																																					
Housing material		Thermoplastic UL94 V-0																																																																					
Operating temperature	Tu	-40/+85°C																																																																					
Protection rating		IP20																																																																					
Failsafe mode		Disconnection from AC network																																																																					
Disconnection indicator		1 mechanical indicator by pole																																																																					
Remote signaling of disconnection		Output on changeover contact																																																																					
Dimensions		See diagram																																																																					
Disconnectors																																																																							
<table border="1"> <tr><td>Thermal disconnecter</td><td></td><td>Internal</td></tr> <tr><td>Installation ground fault breaker</td><td></td><td>Type 'S' or delayed</td></tr> <tr><td>Fuses</td><td></td><td>Fuse assembly: SFD1-25-20S / or Fuses Type gG 315 A</td></tr> </table>			Thermal disconnecter		Internal	Installation ground fault breaker		Type 'S' or delayed	Fuses		Fuse assembly: SFD1-25-20S / or Fuses Type gG 315 A																																																												
Thermal disconnecter		Internal																																																																					
Installation ground fault breaker		Type 'S' or delayed																																																																					
Fuses		Fuse assembly: SFD1-25-20S / or Fuses Type gG 315 A																																																																					
Standards																																																																							
<table border="1"> <tr><td>Standards compliance</td><td></td><td>IEC 61643-11 / EN 61643-11 / UL1449 ed.5</td></tr> <tr><td>Certification</td><td></td><td>UL Recognized</td></tr> </table>			Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5	Certification		UL Recognized																																																															
Standards compliance		IEC 61643-11 / EN 61643-11 / UL1449 ed.5																																																																					
Certification		UL Recognized																																																																					
Part number																																																																							
2579																																																																							