






CITEL

Type 1+2 PV surge protector - 400 Vdc

DS50PV-400G/12KT1



- Type 1+2 surge protector for Photovoltaic
- Impulse currents Iimp/Itotal : 6.25/12.5 kA (10/350µs)
- Common/Differential mode protection
- Remote signaling (option)
- EN 50539-11 / IEC 61643-31 compliance



V: High-energy varistor
GSG: Specific Gas Tube
Ft: Thermal fuse
t*: Thermal disconnection system
MI: Disconnection indicator

Electrical Characteristics

SPD type	1+2
Network	400 Vdc PV power line
Nominal PV voltage	Uocstc 400 Vdc
Max. PV operating voltage	Ucpv 480 Vdc
Residual Current Leakage current to Ground	Ipe None
PV Permanent Operating current Current consumption at Ucpv	Icpv < 0.1 mA
Follow current	If None
Nominal discharge current 15 x 8/20 µs impulses	In 15 kA
Max. discharge current max. withstand @ 8/20 µs by pole	Imax 40 kA
Total Maximum discharge current max. total withstand @ 8 /20 µs	Imax Total 60 kA
Impulse current by pole max. withstand 10/350µs by pole	Iimp 6.25 kA
Total lightning currentmax. total withstand @ 10/350µs	Itotal 12.5 kA
Current withstand short circuit PV	Iscpv 15 000 A
Connection mode(s)	+/-PE
Protection mode(s)	Common/Differential mode
Protection level +@ In (8/20µs)	Up 3 kV
Protection level +/PE (-/PE)@ In (8/20µs)	Up 1.5 kV

Mechanical Characteristics

Technology	MOV+GDT
Connection to Network	By screw terminals: 2.5-25mm ²
Format	Plug-in modular box
Mounting	Symmetrical rail 35 mm (EN 60715)
Housing material	Thermoplastic UL94 V-0
Operating temperature	Tu -40/+85°C
Protection rating	IP20
Outdoor application	No
Disconnection indicator	2 mechanical indicators
Spare module(s)	DSM50PV-400G/12KT1 + DSM50PVS-400G/12KT1
Remote signaling of disconnection	Option DS50PVS-400G/12KT1 - output on changeover contact
Dimensions	See diagram
Weight	0.358 kg
Disconnectors	
Thermal disconnector	Internal
Fuses	Without
Standards	
Standards compliance	EN 61643-11 / IEC 61643-31
Part number	482932

